

Babel support for the Greek language

Apostolos Syropoulos, Günter Milde

July 11, 2019

Babel-greek is a contributed package providing support for the Greek language and script via the [Babel](#) system. See the [README](#) file for an overview of the `babel-greek` package and links to requirements and related packages.

The file `babel-greek.dtx` ¹ is the literate source for the Babel language definition file `greek.ldf`.

1 Requirements

Typesetting Greek with Babel requires (of course) the [Babel core](#), support for Greek font encodings ([greek-fontenc](#)) and a [text font supporting the Greek script](#).

The [CB Greek fonts](#) created by CLAUDIO BECCARI² are a complete set of 8-bit TeX fonts matching KNUTH’s Computer Modern. The package `cbfonts-fd` sets them up as Greek substitute for the Computer Modern and Latin Modern font families. The `substitutefont` package can be used to set up Greek supplements for other font families (like Times or Palatino).

The [Latin Modern](#) OpenType font that is the default font for XeTeX/LuaTeX does not support the Greek script. The user needs to set up an alternative font like Linux Libertine or DejaVu with [fontspec](#).

2 Usage

To activate Greek support with babel, specify the option `greek`, either as global option or as option to the `babel` package. Remember, that the *last* language option determines the document language, e.g.

```
\usepackage[greek,english]{babel}
```

activates support for Greek in an English document. The default is modern “monotonic” Greek, while

¹ The file described in this section has version number v1.9h and was last revised on 2016/09/07. The original author is Apostolos Syropoulos, code from `kdgreek.sty` by David Kastrup was used.

²Apostolos Syropoulos wishes to thank Claudio Beccari for his patience, collaboration, comments and suggestions.

```
\usepackage[english,greek]{babel}
\languageattribute{greek}{polutoniko}
```

sets the document language to modern Greek with “polytonic” spelling and

```
\usepackage[english,greek]{babel}
\languageattribute{greek}{ancient}
```

sets the document language to ancient Greek.

Both attributes may also be used as modifiers as in

```
\usepackage[greek.polutoniko,english]{babel}
```

and similarly

```
\usepackage[greek.ancient,english]{babel}
```

Version 1.9 fixes the activation of hyphenation patterns: By default, **babel-greek** activates the modern Greek monotonic hyphenation; the attribute/modifier **polutoniko** activates the modern Greek polytonic hyphenation and the attribute/modifier **ancient** activates the ancient Greek hyphenation. 8-bit TeX and XeTeX requires the hyphenation patterns to be pre-loaded in the format file. This is a limitation by TeX, common to all languages. The LuaTeX engine loads hyphenation patterns on demand.

```
\selectlanguage
\foreignlanguage
```

The Babel core provides two commands to switch the active language: The declaration `\selectlanguage{greek}` switches to the Greek language. The macro `\foreignlanguage{greek}{<some text>}` sets its second argument in the Greek language. This is intended for short text parts. For details see the [Babel](#) documentation.

For backwards compatibility, “polytonic” spelling can also be selected via the dummy language **polutonikogreek**. In this case, the language name **polutonikogreek** must also be used for language switches with `\selectlanguage` or `\foreignlanguage`. However, it is not possible to use both options, **greek** and **polutonikogreek** in one document.

2.1 Input of Greek text

There are several alternatives to write Greek text.

- With the packages **inputenc** and [greek-inputenc](#), literal Greek characters can be input using the utf-8, iso-8859-7, or macgreek encoding.

Literal input using the utf-8 encoding is also the standard input method if compiling with the XeTeX and LuaTeX engines.

- The Latin transliteration defined by the LGR font encoding is explained in the file [usage.pdf](#).

- The package `greek-fontenc` defines *LaTeX internal character representation* (LICR) macros for Greek letters and text symbols. It is required by `babel-greek`, so the `\textAlpha ... \textomega` macros are a safe but cumbersome method to input Greek characters.
- The `alphabeta` package bundled with `greek-fontenc` makes the short macro names `\Alpha ... \omega` available in text mode, too.

The `greek-fontenc` bundle has details and examples for all these input methods.

2.2 Greek vs. Latin script

When switching the language to Greek, `babel-greek` ensures that the Greek script is supported. With 8-bit LaTeX, Greek text fonts use a non-standard font encoding³ (LGR) that misses Latin letters. Latin characters in the source are instead interpreted as a transcription for Greek characters. The following macros allow the use of Greek vs. Latin script without changing the active language. The `TextCommand`⁴ `\greekscript` switches to a font encoding supporting the Greek script. The declaration `\greektext` always switches the font encoding to LGR. Both declarations do not change the active language. `\latintext` (defined by the Babel core) can be used to switch back to an encoding supporting the Latin script (deprecated since Babel 3.9i from March 2014).

`\greekscript`
`\greektext`
`\latintext`
`\ensuregreek`
`\textgreek`
`\textlatin`

The macros `\ensuregreek` and `\textgreek` take one argument which is typeset using a font encoding supporting the Greek script. While `\ensuregreek` only switches the font encoding if required, `\textgreek` always uses the LGR font encoding. The Babel core defines a corresponding `\textlatin` macro (deprecated in favour of `\ensureascii` in Babel 3.9i from March 2014).

3 Greek numbering

The Greek alphabetical numbering system, like the Roman one, is still used in everyday life for short enumerations. Unfortunately most Greeks don't know how to write Greek numbers bigger than 20 or 30. Nevertheless, in official editions of the last century and beginning of this century this numbering system was also used for dates and numbers in the range of several thousands. Nowadays this numbering system is primary used by the Eastern Orthodox Church and by certain scholars. It is hence necessary to be able to typeset any Greek numeral up to 999 999. Here are the conventions:

- There is no Greek numeral for any number less than or equal to 0.
- Numbers from 1 to 9 are denoted by letters alpha, beta, gamma, delta, epsilon, stigma, zeta, eta, theta, followed by a mark similar to the mathematical symbol “prime”. (Nowadays instead of letter stigma the digraph

³LaTeX font encodings are described in the *LaTeX font guide* (fntguide.pdf).

⁴For a discussion of TextCommands, see the *LaTeX font guide* (fntguide.pdf), too.

sigma tau is used for number 6. Mainly because the letter stigma is not always available, so people opt to write down the first two letters of its name as an alternative. In our implementation we produce the letter stigma, not the digraph sigma tau.)

- Decades from 10 to 90 are denoted by letters iota, kappa, lambda, mu, nu, xi, omikron, pi, qoppa, again followed by the numeric mark. The qoppa used for this purpose has a special zig-zag form, which doesn't resemble at all the original 'q'-like qoppa.
- Hundreds from 100 to 900 are denoted by letters rho, sigma, tau, upsilon, phi, chi, psi, omega, sampi, followed by the numeric mark.
- Any number between 1 and 999 is obtained by a group of letters denoting the hundreds decades and units, followed by a numeric mark.
- To denote thousands one uses the same method, but this time the mark is placed in front of the letter, and under the baseline (it is inverted by 180 degrees). When a group of letters denoting thousands is followed by a group of letters denoting a number under 1000, then both marks are used.

`\greeknumeral` Using these conventions one obtains numbers up to 999999. The command `\greeknumeral` makes it possible to typeset Greek numerals. There is also an "uppercase" version of this macro: `\Greeknumeral`.

Another system which was in wide use only in Athens, could express any positive number. This system is implemented in package `athnum`.

4 Implementation

The macro `\LdfInit` takes care of preventing that this file is loaded more than once, checking the category code of the `@` sign, etc.

```
1 \ifx\@code
2 \LdfInit\CurrentOption{captions\CurrentOption}
```

When the option `polutonikogreek` was used, redefine `\CurrentOption` to prevent problems later on.

```
3 \gdef\CurrentOption{greek}
```

Hyphenation patterns: When this file is read as an option, i.e. by the `\usepackage` command, `greek` could be an 'unknown' language in which case we have to make it known. So we check for the existence of the three variants of the Greek language `\l@greek`, `\l@monogreek`, and `\l@ancientgreek` to see whether we have to do something here.

```
4 \ifx\l@greek\@undefined
5 \nopatterns{greek}
6 \addialect\l@greek 0\fi
7 \ifx\l@monogreek\@undefined
8 \addialect\l@monogreek 0\fi
```

```

9 \ifx\l@ancientgreek\@undefined
10 \adddialect\l@ancientgreek 0\fi
11 \newcount\bbl@monogreek \bbl@monogreek=\l@monogreek
12 \newcount\bbl@polygreek \bbl@polygreek=\l@greek
13 \newcount\bbl@ancientgreek \bbl@ancientgreek=\l@ancientgreek

```

The `\extragreek` macro is called when switching the language to Greek. We collect code for polytonic and ancient greek in the macros `\extrapolutoniumgreek` and `\extrasancientgreek` and add it later to `\extragreek`.

```

14 \addto\extragreek{\let\l@greek\bbl@monogreek\relax}
15 \addto\extrapolutoniumgreek{\l@greek=\bbl@polygreek}
16 \addto\extrasancientgreek{\l@greek=\bbl@ancientgreek}

```

Now we declare the `polutonio` language attribute.

```

17 \bbl@declare@ttribute{greek}{polutonio}{%

```

This code adds the expansion of `\extrapolutoniumgreek` to `\extragreek` and changes the definition of `\today` for Greek to produce polytonic month names (by re-defining `\gr@month`).

```

18 \expandafter\addto\expandafter\extragreek
19 \expandafter{\extrapolutoniumgreek}%
20 \let\captionsgreek\captionspolutoniumgreek
21 \let\gr@month\gr@c@month

```

We need to take some extra precautions in order not to break older documents which still use the old `polutoniumgreek` pseudo-language option: language switching commands like `\selectlanguage{polutoniumgreek}`, call the `\extrapolutoniumgreek` macro, set the language to `\l@polutoniumgreek` and use `\datepolutoniumgreek` for `\today`. We define aliases:

```

22 \let\l@polutoniumgreek\l@greek
23 \let\datepolutoniumgreek\dategreek
24 \let\extrapolutoniumgreek\extragreek
25 \let\noextrapolutoniumgreek\noextragreek
26 }

```

The `ancient` language attribute is used for classical Greek.

```

27 \bbl@declare@ttribute{greek}{ancient}{%

```

This attribute adds the expansion of `\extrapolutoniumgreek` and `\extrasancientgreek` to `\extragreek` to set up support for multi-accented characters and ancient hyphenation patterns. Auto-strings (captions) are specific to ancient Greek while `\today` uses modern polytonic month names (as there existed incompatible sets of month names and no common calendar in ancient Greece).

```

28 \expandafter\addto\expandafter\extragreek
29 \expandafter{\extrapolutoniumgreek}% multi-accented letters
30 \expandafter\addto\expandafter\extragreek
31 \expandafter{\extrasancientgreek}%
32 \let\captionsgreek\captionsansancientgreek
33 \let\gr@month\gr@c@month % (modern) polytonic month names
34 }

```

5 Font setup

Typesetting Greek texts requires a font with Greek characters:

For 8-bit LaTeX, this package uses fonts with the [LGR font encoding](#). With the XeTeX or LuaTeX engines and Unicode fonts, the user must ensure that the selected font contains the required glyphs. LGR-encoded fonts can also be used alongside Unicode fonts with XeTeX/LuaTeX to enable the input of Greek letters via the Latin transcription provided by this font encoding.

`\greekfontencoding` We test for available font encodings and set `\greekfontencoding` and the internal macro `\bbl@greek@fontencdef` with the name of the font definition file with Greek LICR macros. The fallback is LGR.

```

35 \@ifl@aded{def}{tuenc}{
36   \providecommand*{\greekfontencoding}{TU}
37   \providecommand*{\bbl@greek@fontencdef}{greek-euenc}
38   \renewcommand*{\LastDeclaredEncoding}{TU}
39 }{}
40 \@ifl@aded{def}{eulenc}{
41   \providecommand*{\greekfontencoding}{EU1}
42   \providecommand*{\bbl@greek@fontencdef}{greek-euenc}
43   \renewcommand*{\LastDeclaredEncoding}{EU1}
44 }{}
45 \@ifl@aded{def}{eu2enc}{
46   \providecommand*{\greekfontencoding}{EU2}
47   \providecommand*{\bbl@greek@fontencdef}{greek-euenc}
48   \renewcommand*{\LastDeclaredEncoding}{EU2}
49 }{}
50 \providecommand*{\greekfontencoding}{LGR}
51 \providecommand*{\bbl@greek@fontencdef}{lgrenc}

```

Ensure that the Greek LICR macros are available:

```

52 \@ifl@aded{def}{\bbl@greek@fontencdef}{}{
53   \InputIfFileExists{\bbl@greek@fontencdef.def}{}{
54     \errhelp{I can't find the \bbl@greek@fontencdef.def file
55       for the Greek fonts}%
56     \errmessage{Font support for the Greek script missing.^^J
57       babel-greek can't typeset Greek.^^J
58       Install the "greek-fontenc" package^^J
59       or use XeTeX/LuaTeX with polyglossia.}%
60     \@@end
61   }
62 }

```

`\greekscript` The TextCommand `\greekscript` is a declaration that switches the font encoding to `\greekfontencoding` if the current font encoding does not provide a (typically empty) local variant.

```

63 \ProvideTextCommandDefault{\greekscript}{%
64   \fontencoding{\greekfontencoding}\selectfont
65   \def\encodingdefault{\greekfontencoding}}

```

`\ensuregreek` The TextCommand `\ensuregreek` sets its argument in `\greekfontencoding` if the current font encoding does not provide a (typically empty) local variant.

```
66 \ProvideTextCommandDefault{\ensuregreek}[1]{%
67   \leavevmode{\greekscript #1}}
```

5.1 Fixes for the LGR font encoding

```
68 \@ifl@aded{def}{lgrenc}{%
```

We redefine a few commands in the LGR encoding to work around problems because LGR is no *standard text encoding* but has Greek letters in the places of Latin ones.

```
69 \ProvideTextCommand{\textcopyright}{LGR}{\ensureascii{\textcopyright}}
70 \ProvideTextCommand{\textregistered}{LGR}{\ensureascii{\textregistered}}
71 \ProvideTextCommand{\texttrademark}{LGR}{\ensureascii{\texttrademark}}
72 \let\ltx@amp\&
73 \DeclareTextCommandDefault{\&}{\ltx@amp}
74 \DeclareTextCommand{\&}{LGR}{\ensureascii{\ltx@amp}}
75 \ProvideTextCommand{\SS}{LGR}{\ensureascii{\SS}}
```

`\greek@roman` To prevent roman numerals being typeset in greek letters we need to adopt the internal L^AT_EX commands `\@roman` and `\@Roman`. *Up to version 1.5, the definition caused errors where `\roman` ends up in a situation where the argument needs to be expanded (e.g. Roman page numbers in the ToC).*

`\greek@Roman`

```
76 \def\@roman#1{\expandafter\ensureascii\expandafter{\romannumeral#1}}
77 \def\@Roman#1{\expandafter\ensureascii\expandafter{%
78   \expandafter\@slowromancap\romannumeral#1@}}
```

Now we define two commands that switch to the LGR font encoding. The Babel core defines corresponding commands to switch to a Latin font encoding.

`\greektext` The declaration `\greektext` switches to LGR. For shorter pieces of text the `\textgreek` macro should be used.

```
79 \DeclareRobustCommand{\greektext}{%
80   \fontencoding{LGR}\selectfont
81   \def\encodingdefault{LGR}}
```

`\textgreek` This command takes an argument which is then typeset using the LGR font encoding. In order to avoid many encoding switches it operates in a local scope.

```
82 \DeclareRobustCommand{\textgreek}[1]{\leavevmode{\greektext #1}}
```

`\textol` The [CB Greek fonts](#) contain an outline family. In order to make it available, we define the command `\textol`. (This font-specific macro does not fit in a language definition file and is only kept for backwards compatibility.)

```
83 \def\outlfamily{\usefont{LGR}{cmro}{m}{n}}
84 \DeclareTextFontCommand{\textol}{\outlfamily}
85 }{} % End of LGR fixes.
```

6 Definitions for the Greek language

The next step consists in defining commands to switch to (and from) the Greek language.

```
\greekhyphenmins This macro is used to store the correct values of the hyphenation parameters
\lefthyphenmin and \righthyphenmin.
86 % Yannis Haralambous has suggested this value
87 \providehyphenmins{\CurrentOption}{\@ne\@ne}

\captionsgreek The macro \captionsgreek defines all strings used in the four standard document
classes provided with LATEX.
88 \addto\captionsgreek{%
89   \def\prefacename{\textPi\textrho\acconos\textomicron\textlambda
90     \textomicron\textgamma\textomicron\textfinalsigma}%
91   \def\refname{\textAlpha\textnu\textalpha
92     \textphi\textomicron\textrho\acconos\textepsilon\textfinalsigma}%
93   \def\abstractname{\textPi\textepsilon\textrho\acconos\textiota
94     \textlambda\texteta\textpsi\texteta}%
95   \def\bibname{\textBeta\textiota\textbeta\textlambda\textiota\textomicron
96     \textgamma\textrho\textalpha\textphi\acconos\textiota\textalpha}%
97   \def\chaptername{\textKappa\textepsilon\textphi\acconos\textalpha
98     \textlambda\textalpha\textiota\textomicron}%
99   \def\appendixname{\textPi\textalpha\textrho\acconos\textalpha\textrho
100     \texttau\texteta\textmu\textalpha}%
101   \def\contentsname{\textPi\textepsilon\textrho\textiota
102     \textepsilon\textchi\acconos\textomicron\textmu\textepsilon
103     \textnu\textalpha}%
104   \def\listfigurename{\textKappa\textalpha\texttau\acconos\textalpha
105     \textlambda\textomicron\textgamma\textomicron\textfinalsigma}%
106     \textSigma\textchi\texteta\textmu\acconos\textalpha\texttau
107     \textomega\textnu}%
108   \def\listtablename{\textKappa\textalpha\texttau\acconos\textalpha
109     \textlambda\textomicron\textgamma\textomicron\textfinalsigma}%
110     \textPi\textiota\textnu\acconos\textalpha\textkappa\textomega\textnu}%
111   \def\indexname{\textEpsilon\textupsilon\textrho\textepsilon
112     \texttau\acconos\texteta\textrho\textiota\textomicron}%
113   \def\figurename{\textSigma\textchi\acconos\texteta\textmu\textalpha}%
114   \def\tablename{\textPi\acconos\textiota\textnu\textalpha
115     \textkappa\textalpha\textfinalsigma}%
116   \def\partname{\textMu\acconos\textepsilon\textrho\textomicron
117     \textfinalsigma}%
118   \def\enclname{\textSigma\textupsilon\textnu\texteta\textmu
119     \textmu\acconos\textepsilon\textnu\textalpha}%
120   \def\ccname{\textKappa\textomicron\textiota\textnu\textomicron
121     \textpi\textomicron\acconos\textiota\texteta\textsigma\texteta}%
122   \def\headtoname{\textPi\textrho\textomicron\textfinalsigma}%
123   \def\pagename{\textSigma\textepsilon\textlambda\acconos\textiota
124     \textdelta\textalpha}%

```



```

125 \def\seename{\textbeta\textlambda\acconos\textepsilon\textpi\textepsilon}%
126 \def\alsoname{\textbeta\textlambda\acconos\textepsilon\textpi\textepsilon{}
127 \textepsilon\textpi\acconos\textiota\textsigma\texteta\textfinalsigma}%
128 \def\proofname{\textAlpha\textpi\acconos\textomicron
129 \textdelta\textepsilon\textiota\textxi\texteta}%
130 \def\glossaryname{\textGamma\textlambda\textomega\textsigma
131 \textsigma\acconos\textalpha\textrho\textiota}%
132 }

```

`\captionspolutonikogreek` For texts written in the *πολυτονικό* (polytonic greek) the translations are the same as above, but some words are spelled differently. For now we just add extra definitions to `\captionsgreek` in order to override the earlier definitions.

```

133 \let\captionspolutonikogreek\captionsgreek
134 \addto\captionspolutonikogreek{%
135 \def\refname{\accpsili\textAlpha\textnu\textalpha
136 \textphi\textomicron\textrho\accvaria\textepsilon\textfinalsigma}%
137 \def\indexname{\textEpsilon\accdasia\textupsilon\textrho\textepsilon
138 \texttau\acconos\texteta\textrho\textiota\textomicron}%
139 \def\figurename{\textSigma\textchi\accperispomeni\texteta\textmu\textalpha}%
140 \def\headtoname{\textPi\textrho\accvaria\textomicron\textfinalsigma}%
141 \def\alsoname{\textbeta\textlambda\acconos\textepsilon\textpi\textepsilon{}
142 \accpsili\textepsilon\textpi\acconos\textiota\textsigma\texteta\textfinalsigma}%
143 \def\proofname{\accpsili\textAlpha\textpi\acconos\textomicron
144 \textdelta\textepsilon\textiota\textxi\texteta}%
145 }

```

`\captionsansientgreek` For texts written in ancient Greek, we took the translations from Apostolos Syropoulos' `xgreek` package. For now we just add extra definitions to `\captionsgreek` in order to override the earlier definitions.

```

146 \let\captionsansientgreek\captionsgreek
147 \addto\captionsansientgreek{%
148 \def\prefacename{\textPi\textrho\textomicron\textomicron\acconos\textiota\textmu
149 \textiota\textomicron\textnu}%
150 \def\refname{\accpsili\textAlpha\textnu\textalpha\textphi\textomicron\textrho
151 \textalpha\accvaria\textiota}%
152 \def\abstractname{\textPi\textepsilon\textrho\acconos\textiota\textlambda\texteta
153 \textpsi\textiota\textvarsigma}%
154 \def\bibname{\textBeta\textiota\textbeta\textlambda\textiota\textomicron
155 \textgamma\textrho\textalpha\textphi\acconos\textiota\textalpha}%
156 \def\chaptername{\textKappa\textepsilon\textphi\acconos\textalpha\textlambda
157 \textalpha\textiota\textomicron\textnu}%
158 \def\appendixname{\textPi\textalpha\textrho\acconos\textalpha\textrho\texttau
159 \texteta\textmu\textalpha}%
160 \def\contentsname{\textPi\textepsilon\textrho\textiota\textepsilon\textchi
161 \acconos\textomicron\textmu\textepsilon\textnu\textalpha}%
162 \def\listfigurename{\textKappa\textalpha\texttau\acconos\textalpha\textlambda
163 \textomicron\textgamma\textomicron\textvarsigma}%
164 \textsigma\textchi\texteta\textmu\acconos\textalpha\texttau\textomega\textnu}%
165 \def\listtablename{\textKappa\textalpha\texttau\acconos\textalpha\textlambda

```

```

166 \textomicron\textgamma\textomicron\textvarsigma{}
167 \textpi\textiota\textnu\acconos\textalpha\textkappa\textomega\textnu}%
168 \def\indexname{\textEpsilon\accdasia\textupsilon\textrho\textepsilon\texttau
169 \acconos\texteta\textrho\textiota\textomicron\textnu}%
170 \def\figurename{\textSigma\textchi\accperispomeni\texteta\textmu\textalpha}%
171 \def\tablename{\textPi\acconos\textiota\textnu\textalpha\textxi}%
172 \def\partname{\textMu\acconos\textepsilon\textrho\textomicron\textvarsigma}%
173 \def\enclname{\textSigma\textupsilon\textnu\texteta\textmu\textmu
174 \acconos\textepsilon\textnu\textomega\textvarsigma}%
175 \def\ccname{\textKappa\textomicron\textiota\textnu\textomicron\textpi
176 \textomicron\acconos\textiota\texteta\textsigma\textiota\textvarsigma}%
177 \def\headtoname{\textPi\textrho\accvaria\textomicron\textvarsigma}%
178 \def\pagename{\textSigma\textepsilon\textlambda\accvaria\textiota\textvarsigma}%
179 \def\seename{\accdasiavaria\textomicron\textrho\textalpha}%
180 \def\alsoname{\accdasiavaria\textomicron\textrho\textalpha} \accdasia\textomega\textsigma
181 \textalpha\acconos\textupsilon\texttau\textomega\textvarsigma}%
182 \def\proofname{\accpsili\textAlpha\textpi\acconos\textomicron\textdelta\textepsilon
183 \textiota\textxi\textiota\textvarsigma}%
184 \def\glossaryname{\textGamma\textlambda\textomega\textsigma\textsigma
185 \acconos\textalpha\textrho\textiota\textomicron\textnu}%
186 }

```

`\gr@month` The macro `\dategreek` redefines the command `\today` to produce greek dates.
`\dategreek` The name of the month is now produced by the macro `\gr@month` since it is needed in the definition of the macro `\Grtoday`.

```

187 \def\gr@month{%
188 \ifcase\month\or
189 \textIota\textalpha\textnu\textomicron\textupsilon\textalpha
190 \textrho\acconos\textiota\textomicron\textupsilon \or
191 \textPhi\textepsilon\textbeta\textrho\textomicron\textupsilon
192 \textalpha\textrho\acconos\textiota\textomicron\textupsilon \or
193 \textMu\textalpha\textrho\texttau\acconos\textiota\textomicron\textupsilon
194 \or \textAlpha\textpi\textrho\textiota\textlambda\acconos\textiota
195 \textomicron\textupsilon \or
196 \textMu\textalpha'\textiota\textomicron\textupsilon \or
197 \textIota\textomicron\textupsilon\textnu\acconos\textiota
198 \textomicron\textupsilon \or
199 \textIota\textomicron\textupsilon\textlambda\acconos\textiota
200 \textomicron\textupsilon \or
201 \textAlpha\textupsilon\textgamma\textomicron\acconos\textupsilon
202 \textsigma\texttau\textomicron\textupsilon \or
203 \textSigma\textepsilon\textpi\texttau\textepsilon\textmu
204 \textbeta\textrho\acconos\textiota\textomicron\textupsilon \or
205 \textOmicron\textkappa\texttau\textomega\textbeta
206 \textrho\acconos\textiota\textomicron\textupsilon \or
207 \textNu\textomicron\textepsilon\textmu\textbeta
208 \textrho\acconos\textiota\textomicron\textupsilon \or
209 \textDelta\textepsilon\textkappa\textepsilon\textmu\textbeta
210 \textrho\acconos\textiota\textomicron\textupsilon
211 \fi

```

```

212 }
213 \def\dategreek{%
214   \def\today{\number\day \space \gr@month\space \number\year}}

\gr@c@greek
215 \def\gr@c@month{%
216   \ifcase\month\or
217     \accpsili\textIota\textalpha\textnu\textomicron\textupsilon\textalpha
218     \textrho\acconos\textiota\textomicron\textupsilon \or
219     \textPhi\textepsilon\textbeta\textrho\textomicron\textupsilon
220     \textalpha\textrho\acconos\textiota\textomicron\textupsilon \or
221     \textMu\textalpha\textrho\texttau\acconos\textiota\textomicron
222     \textupsilon \or
223     \accpsili\textAlpha\textpi\textrho\textiota\textlambda
224     \acconos\textiota\textomicron\textupsilon \or
225     \textMu\textalpha\'\' \textiota\textomicron\textupsilon \or
226     \accpsili\textIota\textomicron\textupsilon\textnu
227     \acconos\textiota\textomicron\textupsilon \or
228     \accpsili\textIota\textomicron\textupsilon\textlambda
229     \acconos\textiota\textomicron\textupsilon \or
230     \textAlpha\accpsili\textupsilon\textgamma\textomicron\acconos
231     \textupsilon\textsigma\texttau\textomicron\textupsilon \or
232     \textSigma\textepsilon\textpi\texttau\textepsilon\textmu\textbeta
233     \textrho\acconos\textiota\textomicron\textupsilon \or
234     \accpsili\textOmicron\textkappa\texttau\textomega\textbeta
235     \textrho\acconos\textiota\textomicron\textupsilon \or
236     \textNu\textomicron\textepsilon\textmu\textbeta
237     \textrho\acconos\textiota\textomicron\textupsilon \or
238     \textDelta\textepsilon\textkappa\textepsilon\textmu
239     \textbeta\textrho\acconos\textiota\textomicron\textupsilon
240   \fi
241 }

\Grtoday The macro \Grtoday produces the current date, only that the month and the day
are shown as greek numerals instead of arabic as it is usually the case.
242 \def\Grtoday{%
243   \expandafter\Greeknatural\expandafter{\the\day}\space
244   \gr@c@month \space
245   \expandafter\Greeknatural\expandafter{\the\year}}

\extrasgreek The macro \extrasgreek will perform all the extra definitions needed for the
\noextrasgreek Greek language. The macro \noextrasgreek is used to cancel the actions of
\extrasgreek. For the moment these macros switch the fontencoding (with 8-bit
TeX) and the definition of the internal macros \@alph and \@Alph because in
Greek we do use the Greek numerals.
246 \addto\extrasgreek{\greekscript}
247 \addto\noextrasgreek{\latintext}
248 % \addto\noextrasgreek{\RestoreFontEncoding} % TODO define \RestoreFontEncoding

```

`\gr@ill@value` When the argument of `\greeknumeral` has a value outside of the acceptable bounds ($0 < x < 999999$) a warning will be issued (and nothing will be printed).

```

249 \def\gr@ill@value#1{%
250   \PackageWarningNoLine{babel}{Illegal value (#1) for greeknumeral}}

```

`\anw@true` When a large number with three *trailing* zero's is to be printed those zeros *and*
`\anw@false` the numeric mark need to be discarded. As each 'digit' is processed by a separate
`\anw@print` macro *and* because the processing needs to be expandable we need some helper
macros that help remember to *not* print the numeric mark (`\anwtonos`).

The command `\anw@false` switches the printing of the numeric mark off by making `\anw@print` expand to nothing. The command `\anw@true` (re)enables the printing of the numeric mark. These macros need to be robust in order to prevent improper expansion during writing to files or during `\uppercase`.

```

251 \DeclareRobustCommand\anw@false{%
252   \DeclareRobustCommand\anw@print{}}
253 \DeclareRobustCommand\anw@true{%
254   \DeclareRobustCommand\anw@print{\textdexiakeraia}} % \anwtonos
255 \anw@true

```

`\greeknumeral` The command `\greeknumeral` needs to be *fully* expandable in order to get the right information in auxiliary files. Therefore we use a big `\if`-construction to check the value of the argument and start the parsing at the right level.

```

256 \def\greeknumeral#1{%

```

If the value is negative or zero nothing is printed and a warning is issued.

```

257   \ifnum#1<\@ne\space\gr@ill@value{#1}%
258   \else
259     \ifnum#1<10\expandafter\gr@num@i\number#1%
260     \else
261       \ifnum#1<100\expandafter\gr@num@ii\number#1%
262       \else

```

We use the available shorthands for 1.000 (`\@m`) and 10.000 (`\@M`) to save a few tokens.

```

263         \ifnum#1<\@m\expandafter\gr@num@iii\number#1%
264         \else
265           \ifnum#1<\@M\expandafter\gr@num@iv\number#1%
266           \else
267             \ifnum#1<100000\expandafter\gr@num@v\number#1%
268             \else
269               \ifnum#1<1000000\expandafter\gr@num@vi\number#1%
270               \else

```

If the value is too large, nothing is printed and a warning is issued.

```

271             \space\gr@ill@value{#1}%
272             \fi
273           \fi
274         \fi
275       \fi

```

```

276     \fi
277     \fi
278     \fi
279 }

```

`\Greeknatural` The command `\Greeknatural` prints uppercase greek numerals. The parsing is performed by the macro `\greeknatural`.

```

280 \def\Greeknatural#1{%
281   \expandafter\MakeUppercase\expandafter{\greeknatural{#1}}

```

`\greek@alph` In the previous release of this language definition the commands `\greek@aplh` and `\greek@Alph` were kept just for reasons of compatibility. Here again they become meaningful macros. They are defined in a way that even page numbering with greek numerals is possible. Since the macros `\@alph` and `\@Alph` will lose their original meaning while the Greek option is active, we must save their original value. macros `\@alph`

```

282 \let\latin@alph\@alph
283 \let\latin@Alph\@Alph

```

Then we define the Greek versions; the additional `\expandafters` are needed in order to make sure the table of contents will be correct, e.g., when we have appendixes.

```

284 \def\greek@alph#1{\expandafter\greeknatural\expandafter{\the#1}}
285 \def\greek@Alph#1{\expandafter\Greeknatural\expandafter{\the#1}}

```

Now we can set up the switching.

```

286 \addto\extrasgreek{%
287   \let\@alph\greek@alph
288   \let\@Alph\greek@Alph}
289 \addto\noextrasgreek{%
290   \let\@alph\latin@alph
291   \let\@Alph\latin@Alph}

```

What is left now is the definition of a set of macros to produce the various digits.

`\gr@num@i` As there is no representation for 0 in this system the zeros are simply discarded.
`\gr@num@ii` When we have a large number with three *trailing* zero's also the numeric mark is discarded. Therefore these macros need to pass the information to each other about the (non-)translation of a zero.

```

292 \def\gr@num@i#1{%
293   \ifcase#1\or \textalpha\or \textbeta\or \textgamma\or \textdelta\or
294   \textepsilon\or \textsigma\or \textzeta\or \texteta\or \texttheta\fi
295   \ifnum#1=\z@\else\anw@true\fi\anw@print}
296 \def\gr@num@ii#1{%
297   \ifcase#1\or \textiota\or \textkappa\or \textlambda\or \textmu\or
298   \textnu\or \textxi\or \textomicron\or \textpi\or \textqoppa\fi
299   \ifnum#1=\z@\else\anw@true\fi\gr@num@i}
300 \def\gr@num@iii#1{%

```

```

301 \ifcase#1\or \textrho\or \textsigma\or \texttau\or \textupsilon\or
302 \textphi\or \textchi\or \textpsi\or \textomega\or \textsampi\fi
303 \ifnum#1=\z@\anw@false\else\anw@true\fi\gr@num@iii}

\gr@num@iv The first three ‘digits’ always have the numeric mark, except when one is discarded
\gr@num@v because it’s value is zero.
\gr@num@vi 304 \def\gr@num@iv#1{%
305 \ifnum#1=\z@\else\textaristerikeraia\fi
306 \ifcase#1\or \textalpha\or \textbeta\or \textgamma\or \textdelta\or
307 \textepsilon\or \stigma\or \textzeta\or \texteta\or \texttheta\fi
308 \gr@num@iii}
309 \def\gr@num@v#1{%
310 \ifnum#1=\z@\else\textaristerikeraia\fi
311 \ifcase#1\or \textiota\or \textkappa\or \textlambda\or \textmu\or
312 \textnu\or \textxi\or \textomicron\or \textpi\or \textqoppa\fi
313 \gr@num@iv}
314 \def\gr@num@vi#1{%
315 \textaristerikeraia
316 \ifcase#1\or \textrho\or \textsigma\or \texttau\or \textupsilon\or
317 \textphi\or \textchi\or \textpsi\or \textomega\or \textsampi\fi
318 \gr@num@v}

```

7 Character codes

Greek letters drop diacritics (except dialytika and sub-iota) in UPPERCASE. This is not cared for by the Unicode standard. The file `greek-euenc.def` from `greek-fontenc` contains the required `\lccode` and `\uccode` corrections from the `xgreek` package by Apostolos Syropoulos.

The LGR encoded fonts that are used to typeset Greek with 8-bit TeX define ligatures for characters with diacritics. In order for this to work, some characters need to be considered as letters. These characters are `<`, `>`, `~`, `‘`, `’`, `"` and `|`. Therefore, their `\lccode` is changed when Greek is in effect. In order to let `\uppercase` give correct results, the `\uccode` of these characters is set to a non-existing character to make them disappear. Of course not all characters are needed when typesetting “modern” *μονοτονικό*. In that case we only need the `’` and `"` symbols which are treated in the proper way.

`\greek@tilde` The Greek script uses a number of characters with more than one accent. In LGR encoded fonts combined diacritics can be obtained using Knuth’s ligature mechanism (see `usage.pdf`). Characters we need to have ligatures with are the tilde, the acute and grave accent characters, the rough and smooth breathings, the subscript, and the double quote character. In text input the `~` is normally used to produce an unbreakable space.

```

319 \@ifl@aded{def}{\lgrenc}{%
320 \begingroup
321 \ifundefined{active@char\string!}{\catcode'\!=12\relax}
322 \catcode'\~=12%

```

```

323 \lccode'\!='\~%
324 \lowercase{\def\x{\endgroup
325 \def\greek@tilde{!}}\x}

```

In order to get correct hyphenation we need to set the lower case code of a number of characters. The ‘v’ character has a special usage for the **cb** fonts: in fact this ligature mechanism detects the end of a word and assures that a final sigma is typeset with the proper sign which is different from that of an initial or medial sigma; the ‘v’ after an *isolated* sigma fools the ligature mechanism in order to typeset σ in place of ς . Because of this we make sure its lowercase code is not changed. For “modern” greek we have to deal only with ‘ and " and so things are easy. In order to process the suitable characters and in such a way that hyphenation patterns work also with precomposed characters, it is necessary to declare the lc code for all characters, that can be part of a word. We do this in `\extragreek` because this is a feature of the LGR font encoding (which is the same in all language variants). This means that multi-accented characters are regarded parts of a word (and not non-word characters) also in monotonic spelling.

```

326 \addto\extragreek{%
327 \babel@savevariable{\lccode'v}\lccode'v='v%
328 \babel@savevariable{\lccode'\'}\lccode'\='\'%
329 \babel@savevariable{\lccode'\"}\lccode'\="\'"%
330 % ‘high bit characters’: set in a loop and correct exceptions
331 \@tempcnta=128%
332 \@whilenum\@tempcnta<253\do{%
333 \expandafter\babel@savevariable\expandafter{%
334 \expandafter\lccode\the\@tempcnta}%
335 \lccode\@tempcnta=\@tempcnta
336 \advance\@tempcnta\@ne
337 }%
338 % Fix non-word characters:
339 \lccode151=0%
340 \lccode155=0%
341 \lccode159=0%
342 \lccode199=0%
343 % Fix capital letters:
344 \lccode195=147% GREEK LETTER DIGAMMA
345 \lccode219=240% GREEK CAPITAL LETTER IOTA WITH DIALYTIKA
346 \lccode223=244% GREEK CAPITAL LETTER UPSILON WITH DIALYTIKA
347 }
348
349 \addto\extrapolutonikogreek{%
350 % \l@greek=\bbl@polygreek
351 \babel@savevariable{\lccode'\<}\lccode'\<='\<%
352 \babel@savevariable{\lccode'\>}\lccode'\>='\>%
353 \babel@savevariable{\lccode'\~}\lccode'\~='\~%
354 \babel@savevariable{\lccode'\|}\lccode'\|='\|%
355 \babel@savevariable{\lccode'\'}\lccode'\='\'%
356 }

```

And in order to get rid of all accents and breathings when a string is `\uppercase`d we also change a number of uppercase codes.

```

357 \addto\extragreek{%
358   \babel@savevariable{\uccode'\'}\uccode'\'=\'"%
359   \babel@savevariable{\uccode'\'}\uccode'\'=159% 159 == ^^9f
360 }
361 \addto\extrapolutonikogreek{%
362   \babel@savevariable{\uccode'\~}\uccode'\~=159%
363   \babel@savevariable{\uccode'\>}\uccode'\>=159%
364   \babel@savevariable{\uccode'\<}\uccode'\<=159%
365   \babel@savevariable{\uccode'\|}\uccode'\|=\'"%
366   \babel@savevariable{\uccode'\'}\uccode'\'=159%
367 }

```

For this to work we make the character `^^9f` a shorthand that expands to nothing. In order for this to work we need to make a character look like `^^9f` in TeX's eyes. The trick is to have another character and assign it a different lowercase code. Then execute the macros needed in a `\lowercase` environment. Usually the tilde `~` character is used for such purposes. Before we do this we save its original lowercase code to restore it once we're done.

```

368 \@tempcnta=\lccode'\~
369 \lccode'\~=159
370 \lowercase{%
371   \initiate@active@char{~}%
372   \declare@shorthand{greek}{~}{}}
373 \lccode'\~= \@tempcnta

```

Add composite commands, so that the dialytika is kept or put on the following character of a diphthong with `\MakeUppercase` (see `lgrdef.enc` from the `greek-fontenc` package for details).

```

374 \DeclareTextCompositeCommand{\"}{LGR}{^^9f}{\accdialytika}
375 \DeclareTextCompositeCommand{\'}{LGR}{^^9f}{\LGR@hiatus}
376 \DeclareTextCompositeCommand{\'}{LGR}{^^9f}{\LGR@hiatus}

```

We can also make the tilde character itself expand to a tilde with category code 12 to make the typing of texts easier.

```

377 \addto\extrapolutonikogreek{\languageshorthands{greek}}%
378 \declare@shorthand{greek}{~}{\greek@tilde}
379 }{} % End of LGR-specific code.

```

8 symbol name aliases

For backwards compatibility, we keep aliases for a few symbols.

```

380 \providecommand*\{anwtonos}{\textdexiakeraia}
381 \providecommand*\{katwtonos}{\textaristerikeraia}
382 \providecommand*\{qoppa}{\textqoppa}
383 \providecommand*\{stigma}{\textstigma}
384 \providecommand*\{sampi}{\textsampi}
385 \providecommand*\{Digamma}{\textDigamma}

```



```

386 \providecommand*\ddigamma{\textdigamma}
387 \providecommand*\vardigamma{\textvardigamma}
388 \providecommand*\euro{\texteuro}
389 \providecommand*\permill{\textperthousand}

```

The macro `\ldf@finish` takes care of looking for a configuration file, setting the main language to be switched on at `\begin{document}` and resetting the category code of `@` to its original value.

```

390 \ldf@finish{\CurrentOption}
391 \end{code}

```